



2nm 360° Red, hoist, silver anodized

200-014G2-H1C

2nm 360° Red, hoist, silver anodized
1 connector

| Specifications | |
|----------------------------------|--|
| Number | 200-014G2-H1C |
| Light Color | Red |
| Dimensions metric | See drawing |
| Certification | This Navigation Light is certified by DNV, the Declaration of conformity and the certificates can be found on www.lopolight.com under Service & Support |
| Intensity | >5.4cd |
| Dimensions imperial | See drawing |
| Approved to | COLREG72,EN14744,IEC 60945,IACS E10,USCG,ABS,M.E.D.,DNV,LR |
| Visibility | 2nm |
| Operating temperature | -25°C to 55°C |
| Materials | Silver anodized aluminum 25μ, PMMA lens, A4 stainless steel screws, Epoxy, Polyurethane |
| Operating Voltage | 10-32VDC |
| EAN | 5704438022638 |
| IP rating | IP68 |
| UPC Code | 879343022761 |
| Connection | M12 connector |
| Current consumption (mA @ 12VDC) | 150 |
| Current consumption (mA @ 24VDC) | 85 |
| Vessel size | Under 12M,12-20M,20-50M |

Specifications

Weight (Kg) 0 Kg

Weight (Oz) 0.00 Oz